



# NOTCH

Manufacturing, Inc.



## 10 BALE TRANSPORTS

Designed for 2000 lbs. bales – 4.5' to 6' diameter. All fabricated components are made with alloy steel, 2-3 times stronger than mild steel. Unique box cradle design for maximum strength. Cradles are not connected to each other, only to the main beam, this allows loading on both sides from either side. Unit comes standard with fenders, optional 2 bale cradle available. Tricycle type steering for 90° turning, and fast hitch for quick easy hook up.



### 22K 10 BALE TRANSPORT - BT10-22K

Bale Capacity: 22,000 lbs.

Main Beam: 12" x 6" x  $\frac{3}{8}$ " tubing

Removable 2 $\frac{3}{4}$ " rear spindles, 2 $\frac{1}{4}$ " front spindles

Standard front wheels: 22.5" x 8.25" x 8 bolt

Rear wheels: 22.5" x 11.25" x 8 bolt

Front axle design has greasable king pin & bushings, grease fittings on all hubs

(Pictured with standard fenders and optional light package)

### 30K 10 BALE TRANSPORT - BT10-30K

Bale Capacity: 30,000 lbs.

Main Beam: 12" x 6" x  $\frac{1}{2}$ " tubing

Removable 3" rear spindles, 2 $\frac{3}{4}$ " front spindle

Standard front wheels: 22.5" x 8.25" x 8 bolt

Rear wheels: 22.5" x 11.25" x 8 bolt

Front axle design has greasable king pin & bushings, grease fittings on all hubs



### OPTIONAL 2 BALE CRADLE - BT2

Bolt on 2 bale cradle, available on all transports in place of fenders



### OPTIONAL LIGHT PACKAGE

Tail lights; running, stop and turn lights

All enclosed in flush mount for protection

### OPTIONAL BRAKE PACKAGE

Electric Brakes available on 22K model only, rear brakes only, with 16" dual wheels (Not pictured)

Notch Manufacturing reserves the right to change its products or their specifications at any time without notice or obligation.

Notch Manufacturing Inc.

23664 State Hwy. 4 • Lake Henry, MN 56362 • 320-243-7248 • Fax: 320-243-7245 • [www.notchmfginc.com](http://www.notchmfginc.com)