




BALE SPEARS

Frame designed for maximum visibility and durability. Removable forged spears.


Spear Sizes: 32", 39", 43", & 49". Universal attachment standard with other attachments available.

SINGLE - BSS



One 39", 43" or 49" spear in the center of the unit and two 24" stabilizer spears on the bottom of the unit, 48" wide

INDUSTRIAL BALE SPEAR - BSSI



Spear comes with one 49" x 2" industrial spear and two 24" stabilizer spears along the bottom of the unit, 48" wide

THREE POINT MOUNTED SPEARS - BS3PS/BS3PD



Available with single or double spears
CAT 2 & 3 narrow
Optional fifth wheel hitch and ball available

DOUBLE - BSD



Two 39", 43" or 49" spears along the bottom of the unit, 48" wide

UNIVERSAL - BSU



Three 32" or 39" spears along the bottom and one 43" or 49" spear in the center of the unit, 48" wide

QUAD ADJUSTABLE DOUBLE - BSQADB



Four 43" or 49" spears with 100" wide frame width, made to move two round bales, 98" wide 18" cylinder stroke to pull round bales together when loading or placing, adjustment 60" - 78" center to center

HIGH DOUBLE - BSHD



Two 39", 43", or 49" spears along the top of the unit, 48" wide

QUAD - DOUBLE BALES - BSQDB



Four 39", 43", or 49" spears along the bottom of the unit, designed to move two round bales, 102" wide

QUAD with Push Off and Hold Down - BSQ-PH



Four 39" spears along the bottom of unit
Made to move up to three large square bales

TRIPLE - BST



Three 32" or 39" spears along the bottom of the unit, 48" wide

QUAD - BSQ



Four 32" or 39" spears along the bottom of the unit, 71" wide

PUSH OFF



Available for Quad or Triple Bale Spears only

Four/Three 39" spears along the bottom of the unit with hydraulic push off

BALE REST



Designed to bolt on to sides of any Bale Spear
Available w/ or w/o spikes