NOTCH
Manufacturing, Inc.

10 BALE TRANSPORTS

Designed for 2,000 lb. bales – 4.5' to 6' diameter

All fabricated components are made with alloy steel

Unique box frame design for maximum strength

Cradles are not connected to each other, only to the main beam, this allows loading both sides from either side

Unit comes standard with fenders, optional 2 bale cradle available

Tricycle type steering for 90˚ turning

Fast hitch for quick easy hook up

22K 10 BALE TRANSPORT - BT10-22K

Bale capacity: 22,000 lbs.

Main beam: 12" x 6" x ⅜" tubing

Removable 2¾" rear spindles, 2¼" front spindles

Standard front wheels: 22.5" x 8.25" x 8 bolt
Rear wheels: 22.5" x 11.25" x 8 bolt

Front axle design has greasable king pin & bushings, grease fittings on all hubs

(Pictured with standard fenders and optional light package)

30K 10 BALE TRANSPORT - BT10-30K

Bale capacity: 30,000 lbs.

Main beam: 12" x 6" x ½" tubing

Removable 3" rear spindles, 2¾" front spindle

Standard front wheels: 22.5" x 8.25" x 8 bolt
Rear wheels: 22.5" x 13.5" x 8 bolt

Front axle design has greasable king pin & bushings, grease fittings on all hubs

OPTIONAL LIGHT PACKAGE

Tail lights: running, stop and turn lights

All enclosed in flush mount for protection

OPTIONAL BRAKE & LIGHT PACKAGE

Light package plus electric rear brakes

Available in the 22K model only

16" dual wheels

OPTIONAL TWO BALE CRADLE

Two bale bolt on cradle in place of fenders

Available on all transports

Notch Manufacturing reserves the right to change its products or their specifications at any time without notice or obligation.

Notch Manufacturing Inc.
23664 State Hwy. 4 • Lake Henry, MN 56362 • 320-243-7248 • Fax: 320-243-7245 • www.notchmfginc.com