NOTCH
Manufacturing, Inc.

COMPACT ATTACHMENTS

ROCK BUCKET
ROCK BUCKET GRAPPLE
ROCK BUCKET DUAL GRAPPLE

Sizes: 52", 58", 65" & 72"

Constructed with 3/8" high tensile steel, 32" heel to toe, 3" tine spacing

Grapple & Dual Grapple have two hydraulic cylinders with casted greasable ends, cylinder covers protect cylinders and hoses

Universal attachment standard, other attachments available

(Compact Grapple and Dual Grapple Rock Buckets pictured)

LOW PROFILE
LOW PROFILE GRAPPLE

Sizes: 54", 60", 66" & 72"

Constructed with 10 gauge high tensile steel, bucket dimensions: 21" high x 28" deep

Standard ½" x 4" cutting edge with holes to accept ½" x 6" double bevel bolt on reversible cutting edge

Grapple has two hydraulic cylinders with casted greasable ends

Cylinder covers protect cylinders and hoses

Universal and Euro attachments standard, other attachments available

(Compact Low Profile and Grapple Low Profile Buckets Pictured)

THREE POINT MOUNTED HITCH

CAT 1 with receiver hitch to move trailers easily

(Receiver not included)

ROOT BUCKET
ROOT BUCKET GRAPPLE
ROOT BUCKET DUAL GRAPPLE

Sizes: 52", 58", 65" & 72"

Constructed with ½" high tensile steel, 32" heel to toe

Available with 4" or 6" tine spacing

Grapple & Dual Grapple have two hydraulic cylinders with casted greasable ends, cylinder covers protect cylinders and hoses, 41" grapple opening

Universal attachment standard, other attachments available

(Compact Dual Grapple Root Bucket with 6" spacing pictured)

TINE FORK
TINE FORK GRAPPLE
TINE FORK DUAL GRAPPLE

Sizes: 52" & 60"

Constructed with high tensile steel, with removable 32" forged tines held in unit with tapered sleeve for strength and tightness

Grapple & Dual Grapple have two hydraulic cylinders with casted greasable ends, cylinder covers protect cylinders and hoses, 45" grapple opening

Universal attachment standard, other attachments available

(Compact Tine Fork and Grapple Tine Fork Buckets pictured)

PALLET FORKS

48" Wide with straight back frame or walk through models available

Has combined fork capacity of 2000 lbs. at 24" load center

42" Domestic solid fork tines adjustable on a domestic alloy steel fork rail

Accessible form front or back

Side steps standard

High visibility back guard with rolled top design, no sharp corners for safe work environment

Universal attachment standard, other attachments available

Notch Manufacturing reserves the right to change its products or their specifications at any time without notice or obligation.

Notch Manufacturing Inc.

23664 State Hwy. 4 • Lake Henry, MN 56362 • 320-243-7248 • Fax: 320-243-7245 • www.notchmfginc.com