NOTCH
Manufacturing, Inc.

FEEDER WAGONS

Unique trust design sides / Outer and inner frame is fastened to the top outside edge of pan for maximum strength, and keeps bottom of pan clear of obstacles for easy cleaning

Fifth wheel type steering allows 90˚ turning / Quick hitch tongue and heavy duty pole latch allows pole to be latched with wheels at any angle

Grease fittings at all pivot points & hubs

Optional rear gate / Optional full or half galvanized side panels

84" FEEDER WAGON - FW84

Sizes: 16', 20' & 24'
Pan material: 10 gauge alloy steel, pan depth: 13"
Top rails: 4" x 2" rectangle tubing, Slant bars: 1½" square tubing
2" King pin with bushings, 2" Spindle (1¾" on the 16')
6 Bolt hubs with grease fittings
Full length rear axle with removable spindles
16" x 6" Wheels standard (15" x 6" wheels on the 16') other wheels available
(Pictured without side panels)

84" HIGH CAPACITY FEEDER WAGON - FW84H

Sizes: 20', 24', 30' & 36'
Constructed like the 90" Feeder Wagon with deeper pan and heavier tubing, but 84" wide

90" FEEDER WAGON - FW90

Sizes: 20', 24', 30' & 36'
Pan material: 10 gauge alloy steel, pan depth: 15½"
Top rails: 4" x 3" rectangle tubing, Slant bars: 1½" square tubing
2" king pin with bushings, 2" front and 2¼" rear spindles
6 bolt hubs in front and 8 bolt hubs in back with greasable fittings
Full length rear axle with removable spindles
16" x 6" wheels standard, other wheels available
(Pictured with full side panels)

90" CABLE FEEDER WAGON - FW90C

Sizes: 20', 24' & 30'
Adjustable cable wraps around entire feeder
(Pictured with full side panels)

OSCILLATING TANDEM MODEL - FW90-T/FW84H-T

Tandem model available in 90" and 84" High Capacity Feeder Wagons
Sizes: 24', 30', 36' & 40'
(90" pictured with full side panels)

Notch Manufacturing reserves the right to change its products or their specifications at any time without notice or obligation.

Notch Manufacturing Inc.
23664 State Hwy. 4 • Lake Henry, MN 56362 • 320-243-7248 • Fax: 320-243-7245 • www.notchmfginc.com