



# NOTCH

Manufacturing, Inc.



## FIFTH WHEEL 8 BALE TRANSPORTS

Designed for 2000 lbs. bales – 4.5' to 6' diameter. All fabricated components are made with alloy steel, 2-3 times stronger than mild steel. Unique box cradle design for maximum strength. Cradles are not connected to each other only to the main beam this allows loading to both sides from either side.



Unit comes standard with fenders, optional 2 bale cradle available

### FIFTH WHEEL 8 BALE TRANSPORT - BT8-5

Bale Capacity: 8 – 2,000 lbs. round bale, 20" load height

Main Beam: 10" x 4" x 5/16" tubing

Dual 16" wheels, electric brakes, oil bath bearings

Unit comes standard with lights

Light kit includes tail lights; running, stop & turn

Adjustable coupler with safety chains, 10,000 lb. jack

Unit is made for non-highway use (30 MPH or less)

Bales must be properly secured when transporting

## DECKED TRANSPORTS



### DECKED TRANSPORT - DT

Bale Capacity: 8 – 2,000 lbs. round bales or 26 – square bales, 24" load height

Deck Size: 102" x 300" (approx.)

1/8" diamond tread plate deck material

2 3/4" rear spindles, 2 1/4" front spindles, grease fittings on all hubs

Standard front wheels: 22.5" x 8.25" x 8 bolt

Rear wheels: 22.5" x 13.5" x 8 bolt

Tricycle type steering for 90° turning

Fast hitch for quick easy hook up

Unit is made for non-highway use (30 MPH or less)

Bales must be properly secured when transporting

Unit comes standard with fender bridge

Optional light kit includes tail lights; running, stop & turn (Standard with brake version)

Optional flares in front and back for use with round bales (Pictured)

Notch Manufacturing reserves the right to change its products or their specifications at any time without notice or obligation.

Notch Manufacturing Inc.

23664 State Hwy. 4 • Lake Henry, MN 56362 • 320-243-7248 • Fax: 320-243-7245 • www.notchmfginc.com