



NOTCH
Manufacturing, Inc.



GRAPPLE ROOT STUMP BUCKETS



RSBG1 - for skid loader and tractors with lifting capacity of 2,500 lbs. or less



RSBG2 - for skid loader and tractors with lifting capacity from 2,500 lbs. to 5,000 lbs



RSBG3 - for pay loaders and tractors with lifting capacity from 5,000 lbs. to 10,000 lbs.

GRAPPLE ROOT STUMP BUCKET - RSBG2



Constructed with alloy and high tensile steel

1" barbed tines with $7\frac{1}{8}$ " spacing, barbed tines give unit better back cutting action

$\frac{1}{2}$ " high tensile steel cutting edge design distributes force among tines

GRSB2 has a $2\frac{1}{2}$ " x 8" hydraulic cylinder with casted greasable ends with a 56" jaw opening

Heat treated cylinder pins for strength and wearability

Cylinder cover and guard protects cylinder and hoses from above and below

$1\frac{3}{4}$ " pivot pins with bushings, greasable at all pivot points

ROOT STUMP BUCKET - RSB2

Grapple root stump bucket base unit, no grapple

Universal and Euro attachments standard, other attachments available

Notch Manufacturing reserves the right to change its products or their specifications at any time without notice or obligation.

Notch Manufacturing Inc.

23664 State Hwy. 4 • Lake Henry, MN 56362 • 320-243-7248 • Fax: 320-243-7245 • www.notchmfginc.com